Using Printer Class USB – Make sure the Port Selection says ON, if not double click the blue bar

Image				
Single Station	Version 1.0.52	Printer Utility		1:47:50 PM
Configure		Response	:	
				Clear
Flash	Command Selection When complete, reset pr Cmd: Print Configuration Form 1	inter to apply updates.	Port Selection	
Boot	Print Configuration Form 2 Set Monochrome Paper Type Set Red/Green Paper Type Set Blue Paper Type Print Logo Information Print all logos Erase all Logos Set USB to Native Set USB to Native Set USB to Comm Class Enable Paper Low Sensor Disable Paper Low Sensor Set 9600 and DTR Set 19200 and DTR Set 38400 and DTR Set 38400 and DTR	Set 19200 and XON Set 38400 and XON Set 57600 and XON Set 115200 and XON Get Batch Status (1B 76) Get Real Time Status (1D 04 04) Disable/Supress Receipt print Compressed Print	Status	
	Set 115200 and DTR		Execute Reset Printer Clear Status	Send
Hybrid	Table Maintenance		Setup	Cancel
Imager Miscellaneous				Exit

Select the Flash button and then navigate to where you saved the .bin file

🖉 Image				
Single Station	Version 1.0.52	Printer Utility		1:49:32 PM
Configure Scripts Flash Boot Hybrid Imager Miscellaneous	Flash File Selection File Name: C: C: Program Files ImmUtility Sample	Response:	Port Selection USB, PRINTER CLASS, ON - Status - Status - Execute Reset Printer Setup	Clear Send Cancel Exit

Select the .bin file and press Send, this will take a few minutes

Image			_	
Single Station	Version 1.0.52	Printer Utility	1:52:45	PM
Configure	Flash File Selection File Name: [:\FIRMWARE\A	Response:	Port Selection USB, PRINTER CLASS, ON	ar
Flash Boot	E thinking to the first t		Status USB open Port 1 File Size is: 917504 Port 1 Number of Sectors to download is: 14 Port 1 Erasing Flash Downloading Port 1 Sector: 0	
Hybrid Imager			Execute Reset Printer Clear Status Sen Setup Cancel	d

 \sim

Flash file loaded successfully. Now select the Boot button

Single Station			
	Version 1.0.52	Printer Utility	1:54:20 PM
		Hesponse:	Clear
Scripts Flash	Flash File Selection File Name: [:\FIRMWARE\A76	60\Flash\189_7600265C_V207\ A COD (202 DIN	.ON
Boot	E [(\ithfilesvr\eng]	 ABOFV207.BIN Status Downloading Port 1 Sec Downloading Port 1 Sec 	tor: 4 tor: 5 tor: 6 tor: 7 tor: 8 tor: 9 tor: 10 tor: 11 tor: 12 tor: 13
		Execute Reset Printer	lear Status Send
Hybrid		Setup	Cancel
Imager			

/

Navigate to the .pbt file and press send

Firmware upgrade is now complete

🖉 Image				
Single Station	Version 1.0.52	Printer Utility		1:57:39 PM
Configure		Response:	[
Scripts Flash Boot	Boot File Selection File Name: C:\A760\A608 C:\ C:\ A760	3V123.PBT	Port Selection USB, PRINTER CLASS, ON Status Downloading Port 1 Sector: 7 Downloading Port 1 Sector: 8 Downloading Port 1 Sector: 9 Downloading Port 1 Sector: 10 Downloading Port 1 Sector: 11 Downloading Port 1 Sector: 12	
Hybrid Imager			Downloading Port 1 Sector: 13 Reseting Port 1 Printer USB open Port 1 Downloading Boot A60BV123.PBT Port 1 Download File is Complete USB open Execute Reset Printer Setup	Send Cancel
Miscellaneous				Exit